

ENOVA ORIGINAL FURNITURE CO.,LTD

Sample Description : OFFICE CHAIR
 Style / Item No. : CELTA
 Buyer : ENOVA ORIGINAL FURNITURE CO.,LTD
 Manufacturer : ENOVA ORIGINAL FURNITURE CO.,LTD
 Supplier : ENOVA ORIGINAL FURNITURE CO.,LTD
 Country of Destination : UNITED STATES


As above test item and its relevant information regarding to the submission are provided and confirmed by the applicant. SGS is not liable to either the test item or its relevant information, in terms of the accuracy, suitability, reliability or/and integrity accordingly.

Sample Receiving Date : Aug 27, 2021
 Test Performing Date : Aug 30, 2021 to Sep 03, 2021
 Test Performed : Selected test(s) as requested by applicant

Test Result Summary

No.	Test(s) Requested	Result(s)	Comments
1	Backrest Strength Test - Static - Type I and II, Backrest Strength Test - Static - Type III, Drop Test – Dynamic, Stability Tests, Arm Strength Test - Vertical – Static, Arm Strength Test - Horizontal – Static and Backrest Durability Test - Cyclic - Type I of ANSI/BIFMA X5.1-2017 (Type I, III)	PASS	/
For further details, please refer to the following page(s)			

Signed for and on behalf of
 SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch



Marco Leung
 Authorized Signatory

scan to see the report



SDHL2108015869FT

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

TESTS AND RESULTS

Test Conducted:

Backrest Strength Test - Static - Type I and II, Backrest Strength Test - Static - Type III, Drop Test – Dynamic, Stability Tests, Arm Strength Test - Vertical – Static, Arm Strength Test - Horizontal – Static and Backrest Durability Test - Cyclic - Type I of ANSI/BIFMA X5.1-2017 General-Purpose Office Chairs – Tests.

No. of Sample:

2 pieces. For more sample information and pictures, please refer to the following page.

Chair Type: Type I, III.

Test and Requirements	Test Results
5 Backrest Strength Test - Static - Type I and II	
<p>5.4.1 Functional Load There shall be no loss of serviceability to the chair when 667 N (150 lbf.) is applied to the backrest at the specified position for one (1) minute. With the backrest at its back stop position, apply a force that is initially 70 degrees ± 10 degrees to the plane of the backrest. The force is not intended to be maintained at 70 degrees ± 10 degrees throughout the loading of the backrest.</p>	PASS
<p>5.4.2 Proof Load There shall be no sudden and major change in the structural integrity of the chair, loss of serviceability is acceptable, when 1001 N (225 lbf.) is applied to the backrest at the specified position for one (1) minute. With the backrest at its back stop position, apply a force that is initially 70 degrees ± 10 degrees to the plane of the backrest. The force is not intended to be maintained at 70 degrees ± 10 degrees throughout the loading of the backrest.</p>	PASS
6 Backrest Strength Test - Static - Type III	
<p>6.4.1 Functional Load There shall be no loss of serviceability to the chair when 667 N (150 lbf.) is applied to the backrest at the specified position for one (1) minute. With the backrest at its back stop position, apply a force that is initially 90 degrees ± 10 degrees to the plane of the backrest. The force is not intended to be maintained at 90 degrees ± 10 degrees throughout the loading of the backrest.</p>	PASS
<p>6.4.2 Proof Load There shall be no sudden and major change in the structural integrity of the chair, loss of serviceability is acceptable, when 1001 N (225 lbf.) is applied to the backrest at the specified position for one (1) minute. With the backrest at its back stop position, apply a force that is initially 90 degrees ± 10 degrees to the plane of the backrest. The force is not intended to be maintained at 90 degrees ± 10 degrees throughout the loading of the backrest.</p>	PASS
7 Drop Test - Dynamic	
<p>7.4.1 Functional Load Test There shall be no loss of serviceability when a test bag weighing 102 kg (225 lb.) is free fell from 152 mm (6 in.) above the uncompressed seat to the specified position on seat. Remove the bag, and set height to its lowest position and repeat the test for chairs with seat height adjustment features.</p>	PASS

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test and Requirements	Test Results
<p>7.4.2 Proof Load Test There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable when a test bag weighing 136 kg (300 lb.) is free fell from 152 mm (6 in.) above the uncompressed seat to the specified position on seat. Remove the bag, and set height to its lowest position and repeat the test for chairs with seat height adjustment features.</p>	<p>PASS</p>
<p>11 Stability Tests</p>	
<p>11.3.1 Rear Stability Test for Type III Chairs Place a support fixture made of a 1.5 mm ± 0.15 mm (0.060 in. ± 0.006 in.) thick polypropylene, 356 mm (14 in.) wide and 711 mm (28 in.) tall against the chair back so that it approximates the contour of the back. Load the chair with 6 disks (10 kg each). Place the first disk on the seat using the Template from Appendix G. As each disk is added to the stack slide it along the lower disk until it contacts the support fixture. Apply a rearward force parallel to the top surface of the highest disk. The location of the force application is 6 mm (0.25 in.) from the top of the disk. For chairs with seat height (as measured at the front of the bottom of the lowest disk when all disks are in the chair) less than 710 mm (28.0 in.), calculate the force as follows: • F = 0.1964 (1195 – H) Newton. H is the seat height in mm. • [F = 1.1 (47 – H) pounds force.]. H is the seat height in inches. For chairs with seat height equal to or greater than 710 mm (28.0 in.), a fixed force of 93 N (20.9 lbf.) shall be applied. The chair shall not tip over.</p>	<p>PASS</p>
<p>11.3.2 Rear Stability Test for Type I and II Chairs Place a support fixture made of a 1.5 mm ± 0.15 mm (0.060 in. ± 0.006 in.) thick polypropylene, 356 mm (14 in.) wide and 711 mm (28 in.) tall against the chair back so that it approximates the contour of the back. Load the chair with 13 disks. Place the first disk on the seat using the Template from Appendix G. As each disk is added to the stack slide it along the lower disk until it contacts the support fixture. If the chair does not tip over and the tilt mechanism does not tilt to its most rearward position (i.e., at its tilt stop) when the disks are placed in the chair, the chair shall also be tested according to 11.3.1 with the chair in the unlocked position. The chair shall not tip over.</p>	<p>PASS</p>

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test and Requirements	Test Results
<p>11.4 Front Stability <u>Test Procedure</u> Apply a vertical load of 61kg (135 lbf.), through a 200 mm (7.87 in.) diameter disk, the center of which is 60 mm (2.4 in.) from the front center edge of the load-bearing surface of the seat. Apply a horizontal force of 20 N (4.5 lbf.) at the same height that the vertical force is applied. The force shall be coincident with the side-to-side centerline of the seat.</p> <p><u>Test Procedure - Alternate</u> This alternate method may be used on chairs that have a seat surface that will support the stability loading fixture without the use of the front-stability loading disk(i.e., hard surfaced seats or seats with minimal cushion). Apply a vertical load of 61kg (135 lbf.), by means of the front stability loading fixture at a point 60 mm (2.4 in.) from the front center edge of the load-bearing surface of the chair. Apply a horizontal force of 20 N (4.5 lbf.) at the same height that the vertical force is applied. The force shall be coincident with the side-to-side centerline of the seat. The chair shall not tip over as the result of the force application.</p>	<p>PASS</p>
<p>12 Arm Strength Test - Vertical - Static</p>	
<p>12.4.1 Functional Load Apply an initially vertical pull force of 750N (169lbs.) to the load adapter which is 127 mm (5 in.) long and at least as wide as the width of the arm shall be attached to the top of the arm rest structure such that the load will be applied at the apparent weakest point that is forward of the chair backrest, for one (1) minute. There shall be no loss of serviceability. For a height adjustable arm, failure to hold its height adjustment position to within 6 mm (0.25 in.) from its original set position as the result of the loading is considered a loss of serviceability.</p>	<p>PASS</p>
<p>12.4.2 Proof Load Apply an initially vertical pull force of 1125N (253 lbs.) to the load adapter which is 127 mm (5 in.) long and at least as wide as the width of the arm shall be attached to the top of the arm rest structure such that the load will be applied at the apparent weakest point that is forward of the chair backrest, for 15 seconds. There shall be no sudden and major change in the structural integrity of the chair. For a height adjustable arm, a sudden drop in height of greater than 25 mm (1 in.) does not meet this requirement. Loss of serviceability is acceptable.</p>	<p>PASS</p>
<p>13 Arm Strength Test - Horizontal - Static</p>	
<p>13.4.1 Functional Load Apply an initially horizontal pull force of 445 N (100 lbf.) to the load adapter which is a loading device or strap, not greater than 25 mm (1 in.) in horizontal width, shall be attached to the arm so that the load is initially applied horizontally to the armrest structure at the apparent weakest point (for armrests that pivot in the horizontal plane, apply the load at the pivot point), for one (1) minute in the outward direction. A functional load applied once shall cause no loss of serviceability.</p>	<p>PASS</p>

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test and Requirements	Test Results
<p>13.4.2 Proof Load Apply an initially horizontal pull force of 667 N (150 lbf.) to the load adapter which is a loading device or strap, not greater than 25 mm (1 in.) in horizontal width, shall be attached to the arm so that the load is initially applied horizontally to the armrest structure at the apparent weakest point (for armrests that pivot in the horizontal plane, apply the load at the pivot point), for 15 seconds in the outward direction. A proof load applied once shall cause no sudden and major change in the structural integrity of the unit. Loss of serviceability is acceptable.</p>	<p>PASS</p>
<p>14 Backrest Durability Test - Cyclic - Type I A weight of 109 kg (240 lb.) shall be secured in the center of the seat. Apply a 445 N (100 lbf.) total force to the backrest at the specified position at a rate between 10 and 30 cycles per minute. For chairs with backrest widths less than or equal to 406 mm (16 in.) at the height of the loading point, apply the load to the backrest for 120,000 cycles. For chairs with backrest widths greater than 406 mm (16 in.) at the height of the loading point, apply the load to the backrest for 80,000 cycles + 20,000 cycles at the position 102 mm (4 in.) to the right of the vertical centerline + 20,000 cycles at the position 102 mm (4 in.) to the left of the vertical centerline. There shall be no loss of serviceability. <i>Note: With the backrest at its back stop position, apply a force that is initially 90 degrees ± 10 degrees to the plane of the backrest. The force is not intended to be maintained at 90 degrees ± 10 degrees throughout the loading of the backrest.</i></p>	<p>PASS</p>

Remark:

1. For the sample information and pictures, please refer to the following page.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SAMPLE INFORMATION AND PICTURES

Weight: 16.65 kg

Overall Dimensions: 715 mm D x 740 mm W x (1170~1300) mm H

Other Dimensions: Base radius 355 mm

Sample as Received



End of Report

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com